



With over 50 years on the market, it is still the strongest press with the best power-to-weight ratio (2" / 77 kg). The SH 7 sets standards for quality and cost-effectiveness due to its narrow, innovative design, high user-friendliness, versatility, and long service life. Its low weight and compact design make the SH 7 perfect for both stationary and mobile use up to 2 inches, as well as for use as a service or reserve press for quick deployment. The proven, lubrication-free sliding bearing technology with a quick-change system reduces maintenance costs, extends service life, and increases precision.





SH 7






SH 7

SH 7 S

Technical Data	SH 7	SH 7 S	Type of dies		Type of dies	
Crimp force (kN/Ton)	2,400/240	3,200/320	 239-xx-Ø-yy		 265	
No grease: 20% less friction	✓	✓				
Control	Control A	Control A	Ø mm	mm	Ø mm	mm
4/6-spiral + 1-pc fittings*	2"	2"	6.8	65	54	100
4-spiral + 2-pc fittings*	2"	2"	9	65	57	100
4/6-spiral + interlock*	1½"	1½"	10	65	62	100
Industry hose	2"	2"	12	65	67	100
90° Elbows	1½"	1½"	14	65	71	100
Max. Crimp range (mm/inch)	82 / 3.23	82 / 3.23	16	65	74	100
Opening (mm/inch)	+24 / +0.94	+24 / +0.94	17	65		
Opening without dies (mm/inch)	110 / 4.33	110 / 4.33	19	65		
Master dies length (mm/inch)	90 / 3.54	90 / 3.54	20	65		
Type of dies	239 - xx/265	239 - xx/265	22	65		
Press path (mm)	8	8	24	65		
Speed (mm/sec)			26	65		
Close	Manuell	Manuell	28	80		
Crimp	0.42	0.42	30	80		
Open	Manuell	Manuell	31	80		
Noise level	70 dBA	70 dBA	32	80		
Drive	0.75 kW 3~VAC	0.75 kW 3~VAC	34	80		
Oil	2.3 l	2.3 l	36	80		
L x W x H (mm)	430 x 367 x 682	430 x 367 x 682	38	80		
Options (kg)	77	77	39	80		
			40	80		
			44	80		
			47	100		
			50	100		
			54	100		
			57**	100		
			62**	100		
Options						
12 VDC/24 VDC	✓	✓				
1 Phase	✓	✓				

* According to the fitting. ** Not suitable for QDC 239.5. Packages page 28 / Accessories and options page 50

Description




The micrometer allows you to easily set the crimping dimensions.




The machine is pre-positioned manually.



The lightest mobile 2"-service crimping machine. Also available in 12 VDC/24 VDC.



265.2 Turntable



SH = Hollow piston press tool