EM 6 | EM 8

UNIFLEX hose cutting machines have been a synonym for the highest precision and robustness for many decades. The solid and compact tools distinguish themselves by their safe and high-quality cutting function. A distinct property is the positioning of the extraordinarily sharp cutting blades close to the powerful motors. This significantly reduces vibration – which is one of the reasons for extreme durability and low maintenance costs.

EM 6 M

EM 8 M

EM 8 P

Unique drive motor with double bearings and large shaft
Reduce scrap with straight cuts
More cuts between sharpening while increasing profits
Less contamination in the shop and in the end product will result in more parts out the door and a better environment in the building
Maximizes motor life, giving you the lowest cost of ownership in the market
Cut faster and generate a more saleable product
Quality steel blade
Long lasting German quality steel blades, lowering the cost of ownership
Compact Design
Ideal for on-site service
ECOLINE Version
High quality for those new to crimping
CE compliant
Brake motor for safety
Security shield

We reserve the right to make technical changes without notice. Options are machine parts that can only be ordered while buying the machine.

Accessories

UVC
Suction device

UHG 14 + UHG 14 ext
Hose-guide

Hose coiling reel UWT 2
+ Hose measuring tool UMS 4

UAT 4
Coiler

USH 4 +
Hose rack

UMS 4 + 514.1
Measuring device



329.1 (for EM 6 M) |
323.1 (for EM 8)

513.1
Plate for USH 4

Standard

330.1
Spark arrestor

EM 6 DC

EM 6 M

EM 6 P

EM 6 Ecoline

EM 8 M

EM 8 P

Technical data	EM 6 DC	EM 6 M	EM 6 P	EM 6 Ecoline	EM 8 M	EM 8 P
Production SAE R 13 & SAE R 15	–	1¼"	1¼"	–	1¼"	1¼"
Workshop SAE R 13 & SAE R 15	2"	2"	2"	2"	2"	2"
SAE R 12	2"	2"	2½"	2"	2½"	2½"
Industrial	2"	3"	3"	2"	4"	4"
Max. outside	Ø 75 mm	Ø 85 mm	Ø 90 mm	Ø 80 mm	Ø 120 mm	Ø 120 mm
Feed	manual	manual	pneumatic	manual	manual	pneumatic
Noise level	93 dBA	90 dBA	90 dBA	90 dBA	90 dBA	90 dBA
Brake motor	–	✓	✓	–	✓	✓
Suction connection	Ø 40 mm	Ø 60 mm	Ø 60 mm	Ø 80 mm	Ø 60 mm	Ø 60 mm
Drive	3,2 kW : 24 VDC	4,6 kW 3~VAC	4,6 kW 3~VAC	2,4 kW 1~VAC	4,6 kW 3~VAC	4,6 kW 3~VAC
Cutting blade	TM C 250 x 2 x 40	TM C 350 x 3 x 30	TM C 350 x 3 x 30	TM C 275 x 3 x 25,4	TM C 400 x 4 x 30	TM C 400 x 4 x 30
L x W x H (mm)	740 x 365 x 610	745 x 690 x 430	820 x 785 x 755	700 x 510 x 700	983 x 760 x 875	983 x 760 x 540
Weight	29 kg	75 kg	110 kg	45 kg	122 kg	140 kg
Accessories						
Bench	✓	✓	✓	✓	✓	✓
Suction device	✓	✓	✓	✓	✓	✓
UVC Adapter	777.153	777.055	777.055	777.056	777.055	777.055
Hose guide (UHG 14)	–	✓	✓	✓	✓	✓

Additional Information

Guide pins ensure straight cuts, which prolongs EM 1 EM 2 blade life.



Blades
TM = plain
TM G = slotted
TM C = coated

Cutting blades

TM C, TM G and TM

High-quality cutting blades:
TM C, TM G and TM.

TM C

Lasts 7 times longer, cuts twice as fast, generates less smoke, less debris in the hose and less heat. Reduces the risk of separation of the rubber from the wire.